



DIVISION OF CONOLOG CORP.

STANDARD TELEMETRY CHANNELS GEN 1, 98 Series and 68 Series

Channel Center Frequencies (Hz)

SERIES HALF BAND- WIDTH	25	30	35 or 42	60	85	120	150	300
CHANNEL SPACING	100	120	170	240	340	480	600	1200
BAUD RATE	50	60	85	120	170	240	300	600
CHANNEL								
1	365	420	425	480	850	600	1020	1360
2	465	540	595	720	1190	1080	1700	2720
3	565	660	765	960	1530	1560	2380	
4	665	780	935	1200	1870	2040	3060	
5	765	900	1105	1440	2210	2520		
6	865	1020	1275	1680	2550	3000		
7	965	1140	1445	1920	2890			
8	1075	1260	1615	2160	3230			
9	1175	1380	1785	2400				
10	1275	1500	1955	2640				
11	1375	1620	2125	2880				
12	1475	1740	2295	3120				
13	1575	1860	2465	3360				
14	1675	1980	2635					
15	1775	2100	2805					
16	1875	2220	2975					
17	2000	2340	3145					
18	2100	2460	3315					
19	2200	2580	3485					
20	2300	2700						
21	2400	2820						
22	2500	2940						
23	2600	3060						
24	2700	3180						
25	2800	3300						
26	2900	3420						
27	3000							
28	3100							
29	3200							
30	3300							
31	3400							
32	3500							